

## SPECIFICATION

Section: Flooring  
 Area of Use: James Hardie HardieDeck™ System  
 System: Colour

### Scope

Install a coloured protective coating to James Hardie HardieDeck™ System to provide a decorative finish.

### Specification Short Format:

**Crommelin DiamondCoat Tintable Sealer and Tint** provides a low sheen finish in a range of colour options. The product has been modified to promote extremely low dirt pick up, making treated areas easier to maintain.

Application	Product & Coverage	Film Thickness
Preparation	Ensure surface is clean and dry	
1 <sup>st</sup> Coat	<b>DiamondCoat Tintable Sealer and Tint</b> @ 7m <sup>2</sup> /L, allow to dry 2 hours	165µm WFT
Sand	Light sand 180 grit	
2 <sup>nd</sup> Coat	<b>DiamondCoat Tintable Sealer and Tint</b> @ 7m <sup>2</sup> /L, allow to dry 2 hour	165µm WFT
Optional 3 <sup>rd</sup> Coat	<b>DiamondCoat Tintable Sealer and Tint</b> @ 7m <sup>2</sup> /L, this additional coat will provide increased protection or more uniform finish.	165µm WFT

### Note:

Construction requirements and site conditions vary. It is recommended by the manufacturer that site inspections are made prior, during and after application from a Crommelin Representative. Specification for your project, including preparation and detailed drawings are available upon request.  
 Contact Crommelin (Free Call 1800 655 711) or [service@crommelin.com.au](mailto:service@crommelin.com.au)

### Disclaimer

Crommelin® and other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks. Any advice, recommendation, information, assistance or service provided by Crommelin® in relation to its products or their use is given in good faith, however is provided without responsibility or liability. Customers need to undertake their own assessment to determine the suitability of a product for the particular use intended. As the performance of any product is

## SPECIFICATION

Section: Flooring  
Area of Use: James Hardie HardieDeck™ System  
System: Colour

subject to a wide variety of different surface types as well as environmental and surface-specific conditions, it is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it performs on the specific surface.