

Paint Specification

Substrate – JAMES HARDIE HARDIEDECK™ SYSTEM
 Brand New – Opaque Exterior

Product code QPP : Quickpave Paving Paint

Description: Haymes Quickpave is a quick drying, high quality water based paving paint with superior long lasting exterior durability. Quickpave dries to a semi gloss finish.



Substrate Preparation

Remove Contaminants

All surfaces must be clean, bare, dry and free of wax, grease and other contaminants. The presence of contaminants can result in insufficient bonding of the coating and can cause product failure.

Substrate Preparation

Removal of all dust is essential for a successful job. Sweep away all dust and debris and hose the surface with clean water. Test for dust by pressing tape on the surface. If the tape has dust particles present more thorough cleaning is required.

Slip Resistance

Haymes Quickpave does not inherently have slip resistance and requires addition of a textured slip resistance additive to achieve slip resistance.

Product Code QPPNS Quickpave Non Slip Additive

DIRECTIONS FOR USE

1. Use full container for 4L of paint. Use 20g for 1L of paint.
2. Stir the contents of the paint can thoroughly.
3. Sprinkle the additive into the paint in small amounts while stirring with a broad flat stirrer
4. Allow the paint to stand for 1 hour before use.

Coating System Summary

First:	QPP - Haymes Quickpave Paving Paint. Thinned with 20% clean water.
Second:	QPP - Haymes Quickpave Paving Paint.

Please refer to product data sheets (PDS) for specific surface preparation and application information

Coating System

Application Methods:	Brush or roller
Application Notes:	<ul style="list-style-type: none">• Do NOT apply if ambient temperature is less than 10°C or greater than 30°C or if conditions will drop below 10°C during the drying period. Do not apply if rain or frost is expected within 48 hours.• All times quoted assume ambient conditions of 25°C and 50% relative humidity. At cooler temperature or higher humidity drying times will be extended.• Stir thoroughly before and during application.• Some colours may require additional coats to achieve full coverage.• Please check the colour for accuracy prior to application. Haymes paint accepts no responsibility for the application of incorrect colours.• Coverage is up to 12m²/L. However, practical spreading rates may vary from theoretical figures depending on substrate porosity, application methods and environmental conditions (eg wind).

Disclaimer

1. To the extent permitted by law, Henry Haymes Pty Ltd ("Haymes Paint") disclaims all warranties, express or implied, including, but not limited to, implied warranties of merchantability and fitness for purpose.
2. While Haymes Paint uses all reasonable efforts to provide accurate and up to date information, it makes no warranties or representations as to the accuracy of the information provided.
3. Each specification is to be used as a guide only, after independent consideration, and at the applicator's risk.
4. Each specification should be read and followed carefully. If you are unsure about any of the information contained in the specification, further technical help on each specification system and product can be obtained by calling Haymes Service Express on 1800 033 431 - 7-days a week, through Haymes Paint's website or emailing Haymes Paint.
5. Any verbal information, assistance or advice provided by Haymes Paint or its representatives is provided without liability and responsibility.
6. Prior to the use of any products listed, applicators should consult and view the Product Data Sheets ("PDS") and Material Safety Data Sheets ("MSDS") available on Haymes Paint's website.
7. Prior to the use of each product recommended, Haymes Paint recommends the applicator test the product on a sample piece of the substrate.
8. Prior to specifying a system, the specifier should thoroughly read the specification system, PDS and SDS.
9. Haymes Paint is not responsible or liable for any risk, liability or result relating to or arising from the selection of a system.
10. Haymes Paint and its associated or related parties are not liable to you or any other person for any loss, damage or injury arising from the use of this specification or from reliance on information set out in this specification, including but not limited to loss suffered in connection with incorrect information.
11. All warranties, representations and implied terms and any liability which may arise in relation to access or use of the specification is expressly excluded by Haymes Paint to the maximum extent permitted by law.
12. Haymes guarantees that products in this specification not chalk, peel or otherwise deteriorate except for fair wear and tear. For this warranty to apply products must be applied to correctly prepared surfaces. This warranty does not cover failure caused by breakdown of any previous coatings. Haymes will supply paint to recoat affected areas should the product not perform as specified above. Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure. Contact Haymes Service Express 1800 033 431
13. All information, text, trademarks, trade names, branding and service marks are owned by Henry Haymes Pty Ltd and are not for general use unless with the express written permission of Henry Haymes Pty Ltd.
14. "Haymes Paint"; "Haymes Colour Directions"; "Haymes Designer Finishes"; "Haymes Rendercoat"; "Quick Pave"; "New Life"; "Aqualac"; "Solashield"; "Colour Expressions"; "Simply Woodcare"; "DeXpress"; "Rendertex"; "Elite"; "Interior Expressions"; "Haymes Natural Series"; "Rustlock"; "Ultratrim" are registered trademarks of Henry Haymes Pty Ltd ABN 14 004 201 638. Nothing in this specification should be construed as granting by implication or otherwise any licence or right to use any trade mark displayed without the written permission of Haymes Paint.

Henry Haymes Pty Ltd trading As Haymes Paint, Waringa Drive Ballarat, Victoria, Australia. ABN 14 004 201 638